

■ CQ性能参数

型 号	口径		流量		扬程 (m)	汽蚀余量 (m) (NPSH)r	功率 (kW)	转速 (r/min)	电压 (V)
	进口	出口	(m ³ /h)	(L/min)					
16CQ-8	16	12	1.8	30	8	0.5	0.18	2900	220/380
20CQ-12	20	15	3.0	50	12	0.5	0.37	2900	220/380
25CQ-15	25	20	6.6	110	15	0.8	1.1	2900	380
32CQ-15	32	25	6.6	110	15	0.8	1.1	2900	380
32CQ-25	32	25	6.6	110	25	0.8	2.2	2900	380
40CQ-20	40	32	10.8	180	20	1	3	2900	380
40CQ-25	40	32	10.8	180	25	1	3	2900	380
40CQ-35	40	32	10.8	180	35	1	4	2900	380
40CQ-50	40	25	10.8	180	50	1	5.5	2900	380
50CQ-25	50	40	14.4	240	25	1.2	4	2900	380
50CQ-35	50	40	14.4	240	35	1.2	5.5	2900	380
50CQ-50	50	32	14.4	240	50	1.2	7.5	2900	380
65CQ-25	65	50	27	450	25	1.8	5.5	2900	380
65CQ-35	65	50	27	450	35	1.8	7.5	2900	380
80CQ-25	80	65	51	850	25	2.8	7.5	2900	380
80CQ-35	80	65	51	850	35	2.8	11	2900	380

■ CQF性能参数

型 号	口径		流量 (m ³ /h)	扬程 (m)	汽蚀余量 (m) (NPSH)r	功率 (kW)	转速 (r/min)	电压 (V)
	进口	出口						
10CQF-3	10	8	0.9	3	7.8	0.025	2900	220
14CQF-5	14	10	1.2	5	7.0	0.12	2900	220/380
16CQF-8	16	10	1.8	8	6.0	0.18	2900	220/380
20CQF-12	20	15	3	12	6.0	0.37	2900	220/380
25CQF-15	25	20	5.4	15	5.0	1.1	2900	380
32CQF-15	32	25	6.6	15	6.0	1.1	2900	380
32CQF-25	32	25	4.8	25	5.5	1.1	2900	380
40CQF-20	40	32	10.8	20	3.5	2.2	2900	380
50CQF-32	50	40	12.5	32	3.5	4.0	2900	380